

**Description**

ETHANOX 4708 is a liquid hindered phenolic blend with excellent oil solubility and handling. Its primary use is as an oxidation and deposit inhibitor in industrial oils and greases.

**Features and Benefits**

- High activity
- Liquid form for easy handling and blending
- Excellent solubility in all types of base stocks, including Group II, Group III and poly-alpha-olefins
- Synergistic with other antioxidants in a variety of industrial oil and engine oil applications
- Effective at extending induction time in the RPVOT ASTM D 2272

**Typical Properties\***

Appearance (visual) ..... colorless or straw yellow liquid  
TBN, mg KOH/g ..... 8.9  
Specific gravity @ 25 °C ..... 0.95  
Viscosity @ 40°C, cSt ..... 7.5  
Flash point, COC, °C ..... 110  
Water content, % ..... ≤0.1

\*These properties are typical but do not constitute a specification either in part or as a whole. Specification data is available on request from sales, customer service or customer technical service.

**Recommended Dosage**

A dosage of 0.15% to 0.75% by weight is used in lubricating oils. Please contact your Albemarle representative for additional application information.

**Safety and Handling Information**

Please refer to the current material safety data sheet, which is available upon request.

**Chemical Registration Number**

CAS: mixture

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries to ensure the accuracy or reliability of the information. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider all information contained herein only as a guide, and should take precautions that the user considers necessary or prudent to promote a safe work environment, such as considering all applicable health and safety hazards, developing safe work practice procedures and properly instructing employees. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the materials or processes mentioned herein in violation of existing or pending patents.